

Matrix clay and concrete roofing tiles: Compatible roof hooks

	Identifying feature	Processing	Notes	Types tiles / roof stones	SingleHook 3S/4S SingleHook 3S long	SolidHook 3S+/4S+	SingleHook 2	SingleHook 1.1	SingleHook Alpin Metal roof plate or metal re- placement tile required!	SingleHook FlatTile Metal replacement tile 2004282/2004440 required!		SolidHook Pfannenziegel	SolidHook Vario 1+2	SolidHook Flat Tile (plain tile single roofing)	SolidHook Flat Tile (plain tile double roofing)	SolidHook slate
Image roof hook							2/1/					1000001/1000096		V		
					2003215 / 2003144 / 2004222	2002390 / 2002402	2003175	2001928	2003155	2004416	2002651	1001508 / 1000653 / 1000764	1000125 / 1000107	1000214	2003073	1000373
Rail system		_			SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail	SingleRail
- Always 2 waterco (left + top) - Rounded front edg sharp-edged - Distance between different and varia	battens very ble	Processing of the bricks at the lower and upper edge is always necessary.	Large overlap of the tiles possible, therefore note the boom length (T) of the roof hook; see pitched roof brochure "Overview of roof fastenings".	1,11	•	•	0	•	•	0	•	•	•	0	0	0
			H ₂		•	•	0	•	•	0	•	•	•	0	0	0
• Only a lateral wat • Visible concrete s on the front side • Usually approx. 3(approx. 42 cm lon • L _A = Distance betwapprox. 31.5 - 34.5	cructure Ocm wide and Ocupation of the control of	Processing of the bricks at the lower edge is always necessary. – except when using the SingleHook 2 on flat concrete block			0	0	•	0	0	0	•	•	•	0	0	0
					•	•	0	•	•	0	•	•	•	0	0	0
• Scaled optics • Same dimensions Plain tiles	(approx. 18 × 38 cm)		Distance between battens: approx. 15 - 17 cm		0	0	0	0	0		0	0	0	•	•	0
1 2	3 4 5 6															

- trial installation recommended